

CERTIFICATE OF COMPLIANCE

Certificate Number E187183
Report Reference E187183-20200423
Date 2022-March-18

Issued to: DAIRYLAND ELECTRICAL INDUSTRIES INC
340 Business Park Cir
Po Box 187
Stoughton WI, 53589-0187 US

**This is to certify that
representative samples of**

ISOLATORS FOR USE ON CATHODICALLY
PROTECTED SYSTEMS FOR USE IN HAZARDOUS
LOCATIONS

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

ANSI/UL 121201 & CSA C22.2 No. 213-17, Nonincendive
Electrical Equipment for Use in Class I and II, Division 2
and Class III, Divisions 1 and 2 Hazardous (Classified)
Locations;
UL 61010-1 & CSA C22.2 No. 61010-1, Safety
Requirements for Electrical Equipment for Measurement,
Control, and Laboratory Use – Part 1: General
Requirements

Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E187183
Report Reference E187183-20200423
Date 2022-March-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Polarization Cell Replacement Decouplers for use in Class I, Division 2, Groups A, B, C, and D Hazardous Locations.

Models PCRX, followed by -3.7kA, -5kA, -10kA, or -15kA, followed by '-'; followed by 3.0/0.5, 3.5/0.5, 4.5/0.5, 6/2, 5.5/2.5, 5/3, 4.5/3.5, 4/4, 5.5/2, 5/2.5, 4.5/3, 4/3.5, 5/2, 4.5/2.5, 4/3, 3.5/3.5, 4.5/2, 4/2.5 or 3.5/3



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

